



# SBS Switchboard Meters

## DC Battery Voltage Meters



25-469

The SBS DC Battery Voltage Meter has relay with ground fault protection, which automatically scans each range every three seconds. Digital and analog outputs are available for SCADA and in any voltage.

### Optional Fault Indicator Specifications

#### Operation:

Produces current pulses between the transmitter and the ground fault. A pulse receiver can trace the line with these pulses to the ground. Circuit breaker in the line can be identified and open to clean the ground from the system.

#### Features:

- On/off switch on front panel
- Automatic selection of grounded line
- Does not interfere with sensitive electronic equipment, radio, etc.

#### Receiver:

- Hand-held Part No. 200A
- Does not contact circuitry
- LED and sound indications

#### Available Output Options:

- 4 to 20 mADC
- 0 to 1 mADC
- DNP 3.0
- Modbus

#### Ordering Information

Add voltage to catalog number to complete:

- 26-328- \_\_\_ Digital DCV Transducer
- 25-321- \_\_\_ Digital DCV Switchboard meter
- 25-327- \_\_\_ Meter/relay/transducer
- 25-469- \_\_\_ V meter, ground meter/ alarm relay (shown)\*

Call for other switchboard meters not shown

*\* Add suffix "-BB" for optional ground fault locator*